



## Transfluid TO-4

### *Description*

Petromark Transfluid TO-4 is a range of mono-grade oils developed as a transmission and drive train oil (TDTO) meeting Caterpillar TO-4 requirements. The additive package used to produce these products ensures excellent friction control, reduces gear wear, minimal brake noise, oxidation stability and excellent brake and transmission life.

### *Applications*

Single grade oils blended for use where a Caterpillar TO-4 type product is recommended. Petromark's Transfluid TO-4 also meets the requirements of Allison C-4 and Komatsu Micro – Clutch. These products meet the API CF performance level which will protect against the misuse of this product when accidentally added to a diesel engine provided the drain interval is reduced.

### *Performance*

- API CF
- Caterpillar TO-4
- Allison C-4
- Komatsu Micro - Clutch

### *Advantages*

- Prolonged life of brakes and transmission
- Minimal brake noise
- Excellent oxidation stability
- Good friction control

<b>Typical Values</b>	Visc @ 40°C (cSt)	Visc @ 100°C (cSt)	VI
Transfluid TO-4 SAE 10W	39.4	6.2	103.37
Transfluid TO-4 SAE 30	98.0	10.8	92.95
Transfluid TO-4 SAE 40	140.0	14.1	97.53
Transfluid TO-4 SAE 50	215.0	19.3	101.36